



**Limora Zentrallager**  
Industriepark Nord 21  
D - 53567 Buchholz  
Tel: +49 (0) 26 83 - 97 99 0  
E-Mail: Limora@Limora.com  
Internet: www.Limora.com

## FITTING INSTRUCTIONS SPIN ON FILTER ADAPTERS

To compensate for the variations in Filter Head tolerances the Spin On consists of three parts Spin On Inner and Outer and an O ring. The variations in tolerances are taken up by the Spin On Outer sliding over the Spin On Inner. The integrity of the seal between the Inner and Outer is maintained by an O ring.

### Fitting instructions for kit number 329275 Jaguar XKE 3.8 E Type

- Remove existing oil filter bowl and sealing ring.
- Match one of the large sealing rings (item 5) with the sealing ring that was removed from the Filter Head and dispose of the other one. Then place the sealing ring in the Filter Head recess.
- Apply grease to the O ring (item 4) and then fit to the spin on inner sub - assembly.
- To ensure that the inner O ring (item 4) is seated correctly slide the Spin On Outer over the Spin On Inner so that the outer seal face sits back from the Filter Head seal when the unit is assembled to the Filter Head.
- Secure the assembly to the Filter Head with the spigot (item 3) tighten the spigot until the O ring contacts the seal face then tighten a further 1/4 of a turn. Push the Spin On Outer home. The oil seal between the Spin On Outer and the Filter Head will be created when the Oil Filter is fitted.
- Fit the Oil Filter in accordance with the manufacturers instructions. Re-tighten after running 100 miles.

We recommend oil filters with 3/4" UNF thread and anti-drain valve, eg Fram PH8 or equivalent.

8288FI Issue C.

#### Kit of Parts

- 1 off Spin On Assembly (item 2)
- 1 off O Ring 3,53mm dia (item 4)
- 2 off Seals (item 5)
- 1 off Spigot (item 3)

#### Filter Head

Note: The Filter Head shown is a schematic representation of a Filter Head. The Filter Head on your car may not look like this.

